



SENGATE

TWIN PHOTOELECTRIC BEAM SENSOR 2PH-30C / 2PH-60C

FEATURES :

- Easy Optical Alignment.
- A.G.C. (Automatic Gain Control) Circuit.
- High Grade Aspheric Lens.
- Rain, Dust & Insect Protection.
- Frost & Dew Protection.
- Adjustable Beam Interruption Period.



FEATURES



A.G.C. Circuit


The A.G.C. (Automatic Gain Control) Circuit continually monitors for gradual changes in the signal's strength caused by weather conditions and adjusts the trigger level accordingly, to maintain proper sensitivity.

Easy Installation

The pole mount brackets supplied will allow installation of two units on a pole at the same height easily.


Adjustable Beam Interruption Period

Beam interruption time can be adjusted according to the peculiarities of each installation site. When protecting a wall or fence, a long interruption time will catch intruders, but let jumping cats or small objects pass through.



Rain, Dust & Insect Protection


The rubber Ring and Rubber Grommets could prevent rain, dust and tiny insects from adversely affecting performance.



SPECIFICATION

Model	2PH-30C	2PH-60C
Detection Range	Outdoor 90" (30m) or less Indoor 180" (60m) or less	Outdoor 180" (60m) or less Indoor 360" (120m) or less
Current Consumption	38mA (Max)	42 mA (Max)
Supply Voltage	10V-30VDC (Non-Polarity)	
Detection System	Infrared Photoelectric	
Infrared Beam	LED pulsed beam	
Response Time	50-700 msec. (Adjustable)	
Alarm Output	Dry connect relay NC/NO. 0.2A/30 VDC Contact action: 0.5 sec to 2 sec ± 10%	
Tamper Switch Output	Dry connect relay NC/NO. 0.2A/30 VDC (N.C. opens when cover is removed.)	
Alarm LED	Receiver : LED Red ON	
Functions	Monitor jack output, AGC circuit, Frost proof cover.	
Alignment Angle	Horizontal ±90° ; Vertical ±5°	
Over-Voltage Protection	10/160µs 150A, 10/1000µs 75A (58V to 77VDC or more)	
Operating Temperature	-13°F to +131°F (-25°C to +55°C)	
Mounting Positions	Indoor / Outdoor	
Wiring	Terminal	
Environment Humidity	95% (max)	
Weight	32.7 oz (925 grams)	
Dimension (W x H x D)	3"x7.1"x3.1" (76x181.5x77.8 mm)	
Cosmetic	PC (Burgundy color)	
Standard Accessories	U-Shaped brackets x2 pcs Attenuation Sheet x1 pcs Screws (M4x20 Self Tapping) x 4 pcs Screws (M4x20) x4 pcs	

DIMENSIONS



Unit : inch(mm)

NO.B2PH60C0301



Taiwan Security Net Co., Ltd. Designing / Manufacturing

No. 4-46 Feng Jen Rd, Kao Tam Village,
Jen Wu Hsiang, Kaohsiung Hsian, Taiwan, R.O.C.
Tel : 886-7-3721111~3 Fax : 886-7-3721114

Web Site : <http://www.sengate.com>
E-Mail : service@sengate.com