

# PIEZO SIREN

## ◆PIEZO SIREN



LD-80



LD-80



LD-A93



LD-105



LD-97



LD-H97

## ◆SIREN WITH STROBE



LD-A92



LD-96



LD-96



LD-96



LD-H96



LD-H96

## ◆FLUSH MOUNT SIREN



LD-98

| Model NO.                   | LD-80   | LD-A93  | LD-105  | LD-97   | LD-H97  | LD-A92  | LD-96   | LD-H96  | LD-98   |
|-----------------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Operating Voltage (VDC)     | 7~14    | 10~14   | 7~14    | 10~14   | 10~14   | 10~14   | 10~14   | 10~14   | 7~14    |
| Current consumption (mA)    | 130     | 130     | 200     | 250     | 130     | 300     | 450     | 300     | 200     |
| Operating frequency (KHZ)   | 1.5~3.5 | 2.4~3.7 | 2.4~3.7 | 2.4~3.7 | 2.4~3.7 | 2.4~3.7 | 2.4~3.7 | 2.4~3.7 | 2.4~3.7 |
| Alarm output (dB)           | 110     | 110     | 110     | 110     | 110     | 110     | 110     | 110     | 110     |
| Reverse polarity protection | ✓       | ✓       | ✓       | ✓       | ✓       | ✓       | ✓       | ✓       | ✓       |
| Weight (gram)               | 47      | 110     | 100     | 120     | 120     | 110     | 120     | 120     | 100     |

## INTRUDER ALARM WITH STROBE



- LD-281 (Negative activated)
- LD-282 (Positive activated)
- LD-283 (W/Back-up Battery Positive activated)
- LD-285 (W/Back-up Battery negative activated)

### Specification:

- Operating voltage : 11V~14V DC (12V Nominal)
- Power consumption : Siren : 200mA  
Strobe : 250mA
- Siren output : 115 decibel
- Strobe luminous flux : 25 lm
- Size (mm) : 241(L)×160(W)×51(H)

### Features:

- Built-in Anti-tamper switch/with Feed-back Terminal
- Weatherproof, UV proof, Hi-impact. (3mm Polycarbonate housing)
- Six strobe lights
- Polarity reverse protection
- Cable-cutting/Movement Activated (LD-283/LD-285)
- Circuit for AUTO-RECHARGING battery (LD-283/LD-285)